IPETRONIK

CAN FD Satellite Interface

Satellite with 4 ISO CAN FD inputs

- Feature connector with GbE, supply and wake function
- Daisy chaining of several satellites
- WoC and NML support
- Configuration with IPEmotion Software
- 9 status LEDs
- Extension unit for ETHOS, ETHOS 2, ARCOS 2, IPE853

CAN Interface	
CAN FD (ISO 11898-1)	4
CAN FD Baud rate	4 Mbaud
Input sockets	1 Plug 18-pin (1379101-1)
Galvanically isolated	No
Wake on CAN (WoC)	Yes (Latens time 60 ms)
No Message Lost (NML)	Yes
Status-LED	4 Rx/Tx for CAN inputs and WoC, 5 ETH link
Power consumption, WoC+NML	2.0 W
Power consumption, WoC	0.06 W
Analog interface	
Galvanic isolated	No
Device	
Voltage supply	6 … 36 VDC
Supply voltage thresholds	Switch-on 6 ±0.3 VDC / Switch-off 6 ±0.3 VDC
Power consumption, typical	2.0 W
Power consumption, standby	0.003 W
Working temperature range	-40 … 85 °C (-40 … 185 °F)
Storage temperature range	-45 … 90 °C (-49 … 194 °F)
IP-Code	IP 40 (ISO 20653 - 2013)
Relative humidity	5 ... 95 %
Dimensions	B109 mm x H35mm x T130 mm (4.29 in x 1.38 in x 5.12 in)
Weight	365 g (0.80 lb)
Configuration interface	Ethernet (1 Gbit)

Änderungen und alle Rechte vorbehalten. Nachdruck und Vervielfältigung, auch auszugsweise sind verboten!
Changes and all rights reserved. Reprinting and reproduction, even in part, are prohibited!
IPETRONIK GmbH & Co. KG • Phone: +49 7221 99 22 - 0 • Web: www.ipetronik.com • E-mail: info@ipetronik.com

Data transfer rate	1 Gbit
Configuration software	IPEmotion
Input sockets	1 Plug 18-pin (1379101-1)
Accessories	
System cable	620-704 LOG ETH-IN cable satellite 666-531 FEATURE / ABK cable 620-708 ETH RJ45 cable CAN satellite,PWR-banana/P 620-702 LOG GB-ETH LEMO 1B 14p cable satellite 620-710 satellite connection cable
Input cable	620-705 CAN-FD/LIN satellite cable 4x CAN/LIN-SUBD9/P

Änderungen und alle Rechte vorbehalten. Nachdruck und Vervielfältigung, auch auszugsweise sind verboten!
Changes and all rights reserved. Reprinting and reproduction, even in part, are prohibited!