

COPYstation 2

Data exchange station for DATAdrive 2 removable data storage

- Supports up to two DATAdrive 2 removable data storage
- 2 x 10 GbE (RJ45) Ports
- 2 x 100 GbE (QSFP28) Ports
- 2 x USB A (3.2)
- Fully automatic data discharge of the removable data storage
- Configuration via web interface
- Fast data upload to the host server via two 100 GbE interfaces



Interfaces	
Slot for removable data storage	2
Interfaces	
RJ45 (10 GbE)	2
QSFP28 (100 GbE)	2 (optional)
USB 3.2-Interfaces	2
Device	
Operating system	Linux (64 bit)
Processor	AMD EPYC™ 7002/7003
Memory (RAM)	16 GB
Internal storage buffer	32 TB (optional)
storage medium	Max. 2 x DATAdrive 2 removable data storage
Power supply	100 ... 240 VAC
Working temperature range	0 ... 40 °C (32 ... 104 °F)
Storage temperature range	0 ... 60 °C (32 ... 140 °F)
IP-Code	IP 20 (ISO 20653 - 2013)
Relative humidity	5 ... 95 %
Dimensions	W19.09 in x H7.01 in x D23.43 in (B485 mm x H178 mm x T595 mm)
Weight	44 lb (20 kg)
Software functions	

Configuration Software	Web interface
File formats for data storage	ZIP, BLF, AVI, WAV, MDF4.x, ASC, PCAP, PCAPNG, DLT
Communication	
IPEcloud / Server Connection	Azure-Cloud / Amazon S3 / SFTP-Server / SMB
Accessories	
DATAdrive 2	removable data storage