

USB camera

IDS uEye XS Autofocus USB camera

- USB 2.0 mini B
- Sensortype CMOS Color
- Frame rate 15 fps (Autofocus)
- Resolution 2.1 MPixel (1920 x 1080)
- USB camera for video recording
- Supported by loggers with IPEmotion RT (2024 R2)
- Mounting tripod adapter 1/4 inch
- Article number: IPE-CAM-007



Device	
Voltage supply	5 VDC
Power consumption, typical	1.1 W
Working temperature range	0 ... 55 °C (32 ... 131 °F)
Storage temperature range	-20 ... 60 °C (-4 ... 140 °F)
IP-Code	IP 30 (ISO 20653 - 2013)
Relative humidity	20 ... 90%
Dimensions	B 23 mm x H 26.5mm x T 21.5mm (0.9 in x 1.04 in x 0.85 in)
Weight	12g (0,05 lb)
Housing material	Metal housing
Accessories	
System cable	IPE-ZUK-250 (3m USB mini cable included)
General	IPE-ZUK-183 USB3.0 (active extension) IPE-CAB-1-050USB2.0 (active extension) IPE-CAB-2-050USB2 (2 port active extension) USB-III-HUB (7 Port USB3.0 Hub) IPE-HWI-CAM-003 (tripod adapter 1/4 inch)