

## IPEcan FD

### 1-channel USB2CAN FD interface

- PC USB bus adapter for CAN / CAN FD networks
- High speed CAN bus input per ISO 11898
- SUB-D 9-pole connector according CiA® Standard 102
- Data output to PC/notebook via USB 2.0
- 1 operation status LED for USB, CAN
- Software integration for IPEmotion



<b>General channel properties</b>	
Channel LED	Yes
<b>Galvanic isolation</b>	
Input ↔ USB (PC)	500 V
<b>Device</b>	
Eingänge	1
Voltage supply	5 VDC - Power supply via USB (PC)
Power consumption, typical	0.8 W (max 200mA @ 5V)
Working temperature range	-40 ... 85 °C (-40 ... 185 °F)
Storage temperature range	-55 ... 100 °C (-67 ... 212 °F)
IP-Code	IP 50 (ISO 20653 - 2013)
Relative humidity	15 ... 95 %
Dimensions	W92 mm x H16 mm x D54 mm (3.62 in x 0.63 in x 2.13 in)
Weight	115 g (0.254 lb)
Configuration interface	USB 2.0 (compatible to USB 1.1 and USB 3.0)
Test standards	EN 55022: 2008-05 EC Directive 2004/108/EG EN 55024: 2003-10
Input sockets	SUB-D 9-pin connector according CiA® Standard 102 PIN assignment
Status LED	Yes
<b>CAN Interface</b>	
CAN	CAN high speed (ISO11898) 2.0A (standard ID), 2.0B (extended ID)
Data transfer rates CAN (high speed)	25 kBit/s ... 1 MBit/s
Data transfer rates ISO CAN FD	25 kBit/s ... 12 MBit/s
<b>Accessories</b>	
System cable	600-359 620-502 620-567

Alle Rechte vorbehalten. Nachdruck und Vervielfältigung, auch auszugsweise sind verboten!

All rights reserved. Reproduction or duplication in part or in whole are forbidden.

IPETRONIK GmbH & Co. KG • Phone: +49 7221 99 22 - 0 • Web: [www.ipetronik.com](http://www.ipetronik.com) • E-mail: [info@ipetronik.com](mailto:info@ipetronik.com)

