

IPEshunt 2

Operating current measurement via automotive fuse carrier

- Mounting at automotive fuse carrier
- Operating current up to 70 A
- Standard output voltage 0 ... 1 V
- Overload protected up to factor 1.5 of rated current
- Direct connection to SENS modules



IPEshunt	
Measurement range	±30/ 70 A (depending on type)
Operating current ±30 A	±0 ... 1.0 V 0.033 V/A
Operating current ±70 A	±0 ... 1 V 0.014 V/A
Offset deviation at ambient temperature 25 °C	±0.04 mV
Temperature effect on offset	±1.2 µV/K
Temperature effect on accuracy	±250 ppm/K
Overload	Max. 1.5 x I nominal (pulse duration max. 1s) Ensure ventilation, avoid thermal overheating
3 dB cut-off frequency	80 Hz (Version 30 A)
Channel current	
Genauigkeit bei Umgebungstemperatur 25 °C	±1 % of reading
Device	
Eingänge	1
Voltage supply	6 ... 15 VDC
Power consumption, typical	< 4 mA
Working temperature range	-40 ... 85 °C (-40 ... 185 °F)
Storage temperature range	-55 ... 125 °C (-67 ... 257 °F)
Dimensions	W30 mm x H35.5 mm x D9 mm (1.02 in x 1.40 in x 0.35 in)
Weight	8 g (0.28 oz)
Housing material	Plastic

Alle Rechte vorbehalten. Nachdruck und Vervielfältigung, auch auszugsweise sind verboten!

All rights reserved. Reproduction or duplication in part or in whole are forbidden.

IPETRONIK GmbH & Co. KG • Phone: +49 7221 99 22 - 0 • Web: www.ipetronik.com • E-mail: info@ipetronik.com

Accessories	
Input cable	600-102 600-105