

MultiDAQ

42 channel multi-channel input: volt, temperature, current, frequency

- 8 channels: V, mA selectable for each input
- 8 sensor excitations (bipolar ± 15 V, up to ± 45 mA)
- 32 channel thermocouple inputs type K (NiCr/NiAl)
- 2 channel universal counter module with sensor excitation
- 2 sensor excitations (unipolar 15 V, up to ± 60 mA)
- Measurement data output to CAN
- Galvanic isolation (inputs, CAN, supply, enclosure)
- Ruggedized and compact modules for harsh environments



Channel volt	
Measurement range SENS	$\pm 0.1 / 0.2 / 0.5 / 1 / 2 / 5 / 10 / 20 / 30 / 50 / 60 / 100$ V
Accuracy at ambient temperature 25 °C	± 0.05 % (bipolar measurement ranges) ± 0.13 % (unipolar measurement ranges)
General channel properties	
Spezialfunktionen	Offset adjust, during measurement, multiple groups
A/D converter	16 bit / SAR (successive approximation register)
Channel sampling rates	1/ 2/ 5/ 10/ min -- 1/ 2/ 5/ 10/ 20 Hz
Channel sampling rates	1/ 2/ 5/ 10/ 50/ 100/ 200/ 500/ 1000/ 2000/ 5000 Hz
Channel sampling rates	1/ 2/ 5/ 10/ 50/ 100/ 200/ 500/ 1000/ 2000 Hz
Aggregate sample rate	16 kHz
Hardware filter (switchable)	150 Hz, Butterworth (8-pole) Accuracy 10 %
Hardware filter (switchable)	Bessel (5-Pol)
Hardware filter (switchable)	1 ... 30 kHz
Hardware filter (fixed)	1 Hz, filter type RC low pass
Channel impedance	10 MΩ
Filter damping at ambient temperature 25 °C	± 1.5 dB (deviation)
Filter damping at ambient temperature -40 ... 125 °C	± 3.0 dB (deviation)
DC compensation damping at ambient temperature 25 °C	± 1.0 dB (deviation)
DC compensation damping at ambient temperatur -40 ... 125 °C	± 3.0 dB (deviation)
Channel LED	Yes
Channel LED	Yes During configuration - blinking Channel status LED responds to detected input signal
Channel temperature	
Measurement range temperature	Type K (NiCr/NiAl) -60 ... 1370 °C (-76 ... 2498 °F)

Alle Rechte vorbehalten. Nachdruck und Vervielfältigung, auch auszugsweise sind verboten!

All rights reserved. Reproduction or duplication in part or in whole are forbidden.

IPETRONIK GmbH & Co. KG • Phone: +49 7221 99 22 - 0 • Web: www.ipetronik.com • E-mail: info@ipetronik.com

Accuracy at ambient temperature 25 °C (77 °F)	±0.025 % over entire measuring range ±0.035 % in the range -60 ... 1000 °C (-76 ... 1832 °F) ±0.035 % ±3 K in the range 1000 ... 1370 °C (1832 ... 2498 °F)
Drift for ambient temperature -40 ... 85 °C	±20 ppm/K
Drift for ambient temperature 85 ... 120 °C	±30 ppm/K
Linearization of sensor characteristic line	Numerical interpolated
Cold junction compensation (CJC)	8 PT100 (1 per 4 channels)
Aggregate sample rate	640 Hz
Channel CNT	
Mode: frequency	0.03 Hz ... 200 kHz
Mode: duty cycle	0.03 Hz (minimum frequency) 0.01 ... 99.99 % 10 kHz (maximum frequency)
Resolution of duty cycle	1 μ or 1/100 fc filter (higher value)
Mode: period duration, pulse duration, pause duration	1 μs (minimum duration) 200 s (maximum duration)
Resolution Period duration, pulse duration, pause duration	1 μ or 1/100 fc filter (higher value)
Drift at ambient temperature -40 ... 85 °C	±1.5 ppm/K
Drift at ambient temperature 85 ... 105°C	±2.5 ppm/K
Drift at ambient temperature 105 ... 125°C	±5.0 ppm/K
Adjustable trigger threshold	±4 V resolution 0.025V ±40 V resolution 0.20 V
Accuracy of trigger threshold at ambient temperature 25 °C	±3 %
Accuracy of trigger threshold at ambient temperature -40 ... 125 °C	±8 %
DC Compensation	0.8 Hz (lower cut-off frequency -3 dB)
Excitation	
Sensor excitation ranges	Unipolar 2.5/ 5/ 7.5/ 10/ 12.5/ 15V
Accuracy excitation at ambient temperature 25 °C	±5.0 %
Drift for ambient temperature -40 ... 85 °C	±40 ppm/K
Sensor excitation current	60 mA (for V output ±2.5 / ±15.0 V)
Galvanic isolation	
Input ↔ module power supply	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input ↔ CAN	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input ↔ enclosure	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input ↔ input	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input ↔ excitation	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)

Device	
Eingänge	42
Maximum input protection voltage (channel)	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Voltage supply	6 ... 36 VDC
Supply voltage thresholds	On 9 ±0.3 VDC / Off 6 ±0.3 VDC
Power consumption, typical	6.0 W (all excitations off)
Working temperature range	-40 ... 85 °C (-40 ... 185 °F)
Storage temperature range	-55 ... 125 °C (-67 ... 257 °F)
IP-Code	IP 54 (ISO 20653 - 2013)
Relative humidity	5 ... 95 %
Dimensions	W261 mm x H116 mm x D55 mm (10.28 in x 4.57 in x 2.17 in)
Weight	1950 g (4.30 lb)
Configuration interface	CAN high speed
Data transfer rate	Software selectable up to 1 MBit/s (ISO11898-2)
Input sockets	Lemo EGG 1B 307 (7-Pin) Miniature TE plug green (DIN IEC 584)
Status LED	Yes
Accessories	
System cable	620-561 620-502 620-567 M-CAN-ABS 620-560
Input cable	600-857 600-858 600-866 670-807 670-810